

SAFETY DATA SHEET

Slickcoat-A

Foundation Technologies, Inc. encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

Section 1. Product and company identification

GHS product identifier: See above Identifiers

SDS Number: SFTSCA0715 **Product type:** Dispersion

Material uses: **Epoxy Silicone Resin Systems**

Manufacturer/Supplier/

Importer: Foundation Technologies, Inc.

> 1400 Progress Industrial Blvd Lawrenceville GA 30043

Telephone 800-773-2368 / 678-407-4640

Customer Information Email: info@foundationtechnologies.com

For additional health and safety or regulatory information, call **Telephone:**

678-407-4640

Emergency telephone numbers: CHEMTREC US Domestic Emergency 800-424-9300

CHEMTREC International Emergency 703-527-3887



Section 2. Hazards identification

GHS Classification

Reproductive toxicity: Category 2

GHS Label element Hazard pictograms:



Signal Word: Warning

Classification of the substance

or Mixture: Skin, eye, and mucous membrane irritant.

Can cause damage to organs (liver, kidney damage) through

prolonged or repeated exposure.

Precautionary statements

General: Not applicable.

Prevention: Wear protective gloves.

Wear eye or face protection.

Use general exhaust. Do not breathe vapor.

Do not eat, drink, or smoke when using this product.

Wash hands thoroughly after handling.

Response: IF ON SKIN:

Wash with plenty of soap and water. Take off contaminated clothing.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs, get medical attention.

IF IN EYES:

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists, get medical attention.

Storage: Protect against physical damage.

DO NOT FREEZE. Store at room temperature, above 40° F.

Version: 2a Date of Issue/Date of Revision: 12/07/2015 Date of Previous Issue: 06/01/2015 Slickcoat-A (SFTSCA0715) Page 2 of 12



Disposal: Dispose of contents and container in accordance with all local,

regional, national, and international regulations.

Other hazards which do not result

in classification: None known.

Section 3. Composition/information on ingredients

Substance/mixture: Mixture

Ingredient name	% by weight	CAS number
Epoxy Silicone Emulsion (Proprietary)	33 to 50%	
2-Propoxyethanol	5	2807-30-9
Water	42	7732-18-5
Mica/Clay Filler	20 to 3	12001-26-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the

> upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If

necessary, call a poison center or physician.

Inhalation: No harm anticipated from materials in quantities packaged. If any

abnormalities occur such as a headache, remove victim to fresh air

and keep at rest in a position comfortable for breathing.

Skin contact: Wash with soap and water.

Ingestion: Induce vomiting if large amount of material is swallowed.

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media: None known.

Version: 2a Date of Issue/Date of Revision: 12/07/2015 Date of Previous Issue: 06/01/2015 Page 3 of 12



Special exposure hazards: Promptly isolate the scene by removing all persons from the vicinity of

the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Hazardous thermal decomposition

Products: Decomposition products may include the following materials:

carbon oxides aldehydes acids

other organic compounds

Special protective equipment for

fire-fighters:

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautionsNo action shall be taken involving any personal risk or without suitable

training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8 of SDS). Do not breathe dust,

vapor, mist, or gas.

Environmental precautions Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains, and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

Methods for cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Dilute with

water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a

licensed waste disposal contractor.

Large spill Stop leak if without risk. Move containers from spill area. Approach

release from upwind. Prevent entry into sewers, water courses,

basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite, or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for



emergency contact information and section 13 of SDS for waste disposal.

Section 7. Handling and storage

Handling

Put on appropriate personal protective equipment (see section 8 of SDS). Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Workers should wash hands and face before eating, drinking, and smoking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Do not breathe dust, vapor, mist, or

Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Occupational exposure limits

No exposure standard allocated.

Consult local authorities for acceptable exposure limits.

Recommended monitoring

Procedures: If this product contains ingredients with exposure limits, personal,

> workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures

and/or the necessity to use respiratory protective equipment.

Engineering measures: Use only with adequate ventilation. Use process enclosures, local

> exhaust ventilation, or other engineering controls to keep worker exposure to airborne contaminants below any recommended or

statutory limits.

Version: 2a Date of Issue/Date of Revision: 12/07/2015 Date of Previous Issue: 06/01/2015 Page 5 of 12



Hygiene measures: Wash hands, forearms, and face thoroughly after handling chemical

products, before eating, smoking, and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are

close to the workstation location.

Personal Protection

Respiratory Use a properly fitted, air-purifying or air-fed respirator complying with

an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product, and the safe working limits of the

selected respirator.

Hands Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products

if a risk assessment indicates this is necessary.

Eyes Safety eyewear complying with an approved standard should be used

when a risk assessment indicates this is necessary to avoid exposure to

liquid splashes, mists, or dusts.

Skin Personal protective equipment for the body should be selected based on

the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state: Liquid **Color:** White

Odor: Faint odor Odor threshold: Not available

pH: Not available

Melting point/Freezing point: Not available

Boiling point: $100^{\circ} \text{ C } (212^{\circ} \text{ F})$

Flash point: Setaflash Closed Cup: 200° F

Burn time: Not available

Version: 2a Date of Issue/Date of Revision: 12/07/2015 Date of Previous Issue: 06/01/2015

Slickcoat-A (SFTSCA0715)

Page 6 of 12



Foundation Technologies

Slickcoat-A SDS

Burning rate: Not available

Evaporation rate: (BuAc=1): Slower than Butyl Acetate

Flammability (solid, gas): Lower and upper explosive Not available

(flammable) limits:

Lower: Not available **Upper:** Not available

Vapor pressure: (mm Hg): < 21 mm Hg @20° C

Vapor density: Lighter than air

Relative density: 1.07

1,080 kg/m3 **Density:**

Solubility: Not available Solubility in water: Miscible

Partition coefficient: n-

Octanol/water

Not available

Auto-ignition temperature: Not available

Decomposition temperature: Not available **SADT:** Not available

Dynamic: Not available Viscosity:

Kinematic: Not available

Other information

No additional information.

Section 10. Stability and reactivity

Reactivity: Stable under normal conditions.

Chemical stability: The product is stable.

Possibility of hazardous

reactions: Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid: Avoid exposure – obtain special instruction before use.

Incompatible materials: No specific date.

Version: 2a Date of Issue/Date of Revision: 12/07/2015 Date of Previous Issue: 06/01/2015 Page 7 of 12



Hazardous decomposition

products: Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Other Hazards: Reacts with considerable heat release with some curing agents. Heating

> this substance above 300° F in the presence of air may cause slow oxidative decomposition; above 500° F polymerization may occur.

Section 11. Toxicological information

Information on toxicological effects

Irritation/Corrosion

Skin: Not available **Eyes:** Not available **Respiratory:** Not available

Sensitization

Skin: Not available **Respiratory:** Not available

Mutagenicity

Conclusions/Summary: Not available

Carcinogenicity

Conclusions/Summary: Not available

Aspiration hazard

Not available

Information on the likely routes

of exposure: Not available

Potential acute health effects

Eye contact: Causes serious eye irritation.

Inhalation: Harmful if inhaled.

Skin contact: Cause skin irritation. May cause an allergic skin reaction.

Ingestion: Irritation to mouth, throat, and stomach.

Version: 2a Date of Issue/Date of Revision: 12/07/2015 Date of Previous Issue: 06/01/2015 Page 8 of 12



Symptoms related to the physical, chemical, and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation: No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects: Not available **Potential delayed effects:** Not available

Long term exposure

Potential immediate effects: Not available **Potential delayed effects:** Not available

Potential chronic health effects

General: Causes damage to organs through prolonged or repeated

exposure:

Once sensitized, a several allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity:

No known significant effects or critical hazards.

Numerical measures of toxicity

Acute Toxicity estimates

Not available

Version: 2a Date of Issue/Date of Revision: 12/07/2015 Date of Previous Issue: 06/01/2015 Slickcoat-A (SFTSCA0715) Page 9 of 12



Section 12. Ecological information

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods:

The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International transport regulations

Regulatory Information	UN/NA number	Proper shipping name	Classes/*PG	Reportable Quantity (R Q)
CFR		Non-regulated		
TDG		Non-regulated		
IMO/IMDG		Non-regulated		
IATA (Cargo)		Non-regulated		
*DC: Doolsing or	oun			

*PG: Packing group

Special precautions for user: Transport within user's premises: always transport in closed containers

> that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Version: 2a Date of Issue/Date of Revision: 12/07/2015 Date of Previous Issue: 06/01/2015 Page 10 of 12



Section 15. Regulatory information

United States

HCS Classification: Irritating material

> Sensitizing material Target organ effects

U.S. Federal regulations: SARA 302 Extremely Hazardous Substances: None required.

> SARA 302/304/311/312 hazardous chemicals: None required. SARA 311/312 MSDS distribution - chemical inventory - hazard **identification:** Immediate (acute) health hazard, Delayed (chronic)

health hazard

California Prop. 65: None required.

United States inventory

(TSCA 8b): All components are listed or exempted.

Canada

WHMIS (Canada): Class D-1B: Material causing immediate and serious toxic effects

(Toxic).

Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

Canadian NPRI: None required.

CEPA Toxic substances: None required.

International regulations

International lists: Australia inventory (AICS): Not determined.

Canada inventory: At least one component is not listed in DSL but all

such components are listed in NDSL.

Japan inventory: All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Korea inventory: Not determined.

New Zealand Inventory (NZIoC): Not determined. Philippines inventory (PICCS): Not determined.

United States inventory (TSCA 8b): All components are listed or

exempted.


Taiwan inventory (CSNN): All components are listed or exempted.

Version: 2a Date of Issue/Date of Revision: 12/07/2015 Date of Previous Issue: 06/01/2015 Slickcoat-A (SFTSCA0715) Page 11 of 12



Section 16. Other information

NFPA Ratings:



Notice to reader

The information provided herein was believed by Foundation Technologies, Inc. (Foundation Technologies) to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Foundation Technologies are subject to Foundation Technologies' terms and conditions of sale. FOUNDATION TECHNOLOGIES MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY FOUNDATION TECHNOLOGIES, except that the product shall conform to Foundation Technologies' specifications. Nothing contained herein constitutes an offer for the sale of any product.

Slickcoat Trademark of Foundation Technologies, Inc.