

Material Safety Data Sheet

**Foundation
Technologies, Inc.®**

PO Box 491718
Lawrenceville, GA 30049
678.407.4640

Slickcoat™

I. Physical Data

Boiling Point: >212°F.
Specific Gravity (H2O=1): >1.0
Vapor Pressure (mm Hg and Temperature): < 21mm Hg @ 20°C
Melting Point: N/A
Vapor Density (Air=1): Lighter than air
Evaporation Rate (Butyl Acetate=1): Slower than Butyl Acetate
Solubility in Water: Miscible

II. Material Identification and Information

COMPONENTS - Chemical Name & Common Names (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	%	OSHA ACGIH OTHER LIMITS		
		PEL	TLV	RECOMMENDED
Epoxy Silicone emulsion Cas# 025068-38-6	54
2-Propoxyethanol Cas# 0028007-30-9	2
... Not established.				
Non-Hazardous Ingredients	44			
TOTAL	100			

III. Fire and Explosion Hazard Data

Flash Point and Method Used: 200°F TCC
Auto-Ignition Temperature: N/A
Flammability Limits in Air, % by Volume: N/A
LEL: N/A
UEL: N/A
Extinguisher: Dry foam, Carbon Dioxide
Special Fire Fighting Procedures: None
Unusual Fire and Explosion Hazards: None

IV. Health Hazard Data

Primary Routes of Entry: Inhalation, Ingestion, Skin Absorption
Effects of Overexposure: Possible skin rash. May damage eyes. Contains solvents that have the potential to cause headaches, nausea, dizziness and respiratory irritation.
Emergency and First Air Procedures: Wash hands and eyes with plenty of soap and water. If ingested drink plenty of water. In case of exposure to a high concentration of vapor or mist remove person to fresh air. If breathing has stopped administer artificial respiration and seek medical attention. Call Physician.

V. Reactivity Hazard Data

Stability: __UNSTABLE : X STABLE
Conditions to Avoid: Open flame, spark, and high heat.
Incompatibility (Materials to Avoid): Strong acids, bases, amines can cause polymerization
Hazardous Decomposition Products: may include carbon dioxide or carbon monoxide
Hazardous Polymerization: : X MAY OCCUR ___ WILL NOT OCCUR
Conditions to Avoid:

VI. Control and Protective Measures

Respiratory Protection (Specify Type):
Protective Gloves: Chemical resistant gloves

Eye Protection: Chemical resistant goggles

Ventilation to be Used:

Local Exhaust

Mechanical (general)

Special

Other

Other Protective Clothing and Equipment: Wash after using. Segregate all cleaning apparatus.

Hygienic Work Practices: Avoid contamination of skin.

VII. Precautions for Safe Handling and Use / Leak Procedures

Steps to be Taken if Material is Spilled or Released: Wash with water. Dike all spills; absorb with inert material and collect for disposal.

Waste Disposal Methods: Incinerate or use biological treatment in accordance with Federal, State and Local Regulations.

Precautions to be Taken in Handling and Storage Store at room temperature: Mix before using and store at room temperature above 40°F, **DO NOT FREEZE**