


INNOVATIVE ENGINEERED **TIEBACK ANCHOR CHAIRS AND BEAMS**

AN ALTERNATIVE TO TRADITIONAL
WEDGE PLATES, BEARING PLATES
AND WALERS/CSM BEAMS



**NO WELDING
REQUIRED**



**VARIABLE
ANGLES**



**COST
EFFICIENT**



DISCOVER OUR SOLUTIONS

INNOVATIVE REUSABLE SOLUTIONS FOR ANCHORING DIFFERENT WALL TECHNOLOGIES



PROANC40BN

Variable angle:
from 0° until 50°
Anchor diameter:
max. 42 mm/1.65"

PROANC52BN

Variable angle:
from 0° until 50°
Anchor diameter:
max. 52 mm/2"



PRODAM40BN

Variable angle:
from 0° until 50°
Anchor diameter:
max. 42 mm/1.65"

PRODAM52BN

Variable angle:
from 0° until 50°
Anchor diameter:
max. 52 mm/2"



PROBEAMSOIL40N

Variable angle:
from 0° until 50°
Anchor diameter:
max. 42 mm/1.65"
Length:
800 mm/31.5"

PROBEAMSOIL52N

Variable angle:
from 15° until 50°
Anchor diameter:
max. 52 mm/2"
Length:
800 mm/31.5"



PROBEAM30N

Fixed angle:
30° or 45°
Anchor diameter:
max. 32 mm/1.26"
Length:
1,600 mm/63"

Foundation Technologies, Inc.[®]

FAMILY OF BRANDS

1400 Progress Industrial Blvd.
Lawrenceville, GA 30043
470-226-2036
profound@foundationtechnologiesinc.com

1065 Alper Center Drive
Henderson, NV 89052
725-254-2014
west@foundationtechnologies.com

